

# STRENGTH AREA



DATASHEET

## PAVIGYM ENDURANCE

Its high density provides supreme resistance for standard cardio, functional training & free weight areas (medium loads).

# TECHNICAL INFO

Weight		6,8 kg
Density	UNE-53526	1.200 kg/m <sup>3</sup>
Hardness	din 53505	75° Shore A
Water absorption	ASTM D570	0%
Coef. of linear dilatation	0°C-40°C	1,5 10 <sup>-4</sup> °C <sup>-1</sup>
Fire reaction	EN 13501-1	Cfl-s2 (Op. Bfl-s1)
Sound insulation	ISO 10140	15,4 dB


# COMPARATIVE CHART

	PAVIGYM ENDURANCE S&S	PAVIGYM ENDURANCE	RECYCLED RUBBER (ROLLS)
Comfort	*****	***	**
Marks resistance (medium loads)	*****	****	***
Marks resistance (heavy loads)	****	***	**
Sound insulation	*****	***	**
Durability	*****	****	***
Hygienic / Anti-bacterial protection	*****	*****	**
Thermal insulation	*****	*****	***
Water resistance	*****	*****	***
Easy to install & maintain	*****	*****	**

# COLOURS



PAVIGYM LIME



PAVIGYM ORANGE



PAVIGYM CYAN



PAVIGYM RED



PAVIGYM MAGENTA




PAVIGYM PURPLE




PAVIGYM WENGUE




PAVIGYM WALNUT




PAVIGYM A. BROWN




PAVIGYM BEECHWOOD



PAVIGYM B. MARBLE



PAVIGYM JET BLACK




PAVIGYM STONE GREY



INTERLOCKING SYSTEM

To avoid counterfeiting, our tiles are marked with the Pavigym logo



THICKNESS  
7 mm



VIRGIN RUBBER MLECULE  
PERFECT POLYMERIC CHAIN



# STRENGTH AREA

