

FREE WEIGHT AREAS



TECHNICAL DATA SHEET

**PAVIGYM**  
THE BASIS OF FITNESS

**P** PAVIGYM  
ENDURANCE S&S

Extra-thickness for more protection  
against impacts for heavy loads.

# TECHNICAL INFORMATION

Weight		16 kg
Density	UNE-53526	900 kg/m <sup>3</sup>
Hardness	din 53505	75° Shore A
% water absorption	ASTM D570	0%
Coef. linear dilatation	0°C-40°C	10 <sup>-4</sup> °C <sup>-1</sup>
Fire classification	EN 13501-1	Cfl-s1
Formaldehyde emission	EN 717-2	<0,5
Sound insulation	ISO 10140	21 dB

# COMPARATIVE CHART

	PAVIGYM ENDURANCE S&S	PAVIGYM ENDURANCE	RECYCLED RUBBER (ROLLS)
Comfort	*****	***	**
Marks resistance (medium loads)	*****	****	***
Marks resistance (heavy loads)	****	***	**
Sound insulation	*****	***	**
Durability	*****	****	***
Hygienic / Anti-bacterial protection	*****	*****	**
Thermal insulation	*****	*****	***
Water resistance	*****	*****	***
Easy to install & maintain	*****	*****	**


# COLOURS



PAVIGYM WENGUE



PAVIGYM BEECHWOOD



PAVIGYM STONE GREY



PAVIGYM B. MARBLE



PAVIGYM JET BLACK


## SPECIAL COLOURS \*Contact us for more info about availability.



PAVIGYM CYAN



PAVIGYM LIME



PAVIGYM RED




PAVIGYM WALNUT



INTERLOCKING SYSTEM

To avoid product counterfeiting, our tiles are marked with the Pavigym logo



THICKNESS 22 mm



**Top Layer**  
Virgin rubber= resistance and friction

**Bottom Layer**  
Rubber + air = Impact absorption + sound absorption



TOP LAYER VIRGIN RUBBER

# FREE WEIGHT AREAS

**P**AVIGYM  
ENDURANCE S&S

